

Hot Air Blowers TYPE DXC 60 - 100

- Technical Information



LAE Anlagenbau GmbH * Altenwalder Chaussee 94 – 100 * D – 27472 Cuxhaven
Tel : +49 4721 105 0 * FAX : +49 4721 105 210 * E-MAIL : info@lae-cuxhaven.de
Internet : <http://www.lae-cuxhaven.de>

TYPE DXC 60 - 100

This hot air device was specially developed for heating poultry houses in cooperation with insurance companies. The closed consumption chamber makes flying sparks practically impossible.

For propane gas operation and natural gas operation

Optimum use of energy

Insensitive to corrosion



Type	Capacity kW	Gas consumption		Connecting pressure		Gas- connecti on	Air- displacement m ³ /h	Effective heat range m	Weight kg	L x W x H mm
		Natural gas m ³ /h	propane kg/h	Natural gas mbar	propane mbar					
DXC60	60	7,8	5,2	20-25	37-50	¾"	6.000	40	140	2100x 650x1080
DXC80	76	9,9	6,6	20-25	37-50	¾"	8.000	45	150	2100x650x 1080
DXC100	99	12,8	8,6	20-25	37-50	¾"	10.000	45	175	2100x815x 1080

Subject to technical modifications.

* Depending the Wobbe index

Equipment

The DXC is a modulating indirect fired heating system with a closed combustion chamber and flue gas duct.

LAE Anlagenbau GmbH * Altenwalder Chaussee 94 – 100 * D – 27472 Cuxhaven
Tel : +49 4721 105 0 * FAX : +49 4721 105 210 * E-MAIL : info@lae-cuxhaven.de
Internet : <http://www.lae-cuxhaven.de>